



## USE OF CABLE

UL/CSA approved data transmission cable, control and connecting cable predominantly for transmission of analog and digital signals in process controlled facilities in measurement and control technology for lossless data and signal transmission. For fixed laying and flexible applications with undefined cable routing and without tensile stress. Suitable for use in dry and humid rooms. Outdoor use only with UV-protection, no laying underground.



## SPECIAL FEATURES

- largely resistant to acids, bases and specified types of oil
- LABS-/silicone-free (during production)
- recommended for EMC-applications
- capable for soldering, crimp and cut-and-clamp

## REMARKS

- conform to RoHS
- conform to 2014/35/EU-Guideline ("Low-Voltage Directive") CE
- We are pleased to produce special versions, other dimensions, core and jacket colours on request.

## PRODUCT INFORMATION

|                              |                                                                                         |
|------------------------------|-----------------------------------------------------------------------------------------|
| Conductor material:          | Copper strand tinned                                                                    |
| Conductor class:             | 7 resp. 19 wires                                                                        |
| Core insulation:             | PVC                                                                                     |
| Core identification:         | Acc. to DIN 47100 with grey outer sheath acc. to IC colour-code with black outer sheath |
| Stranding:                   | Stranded in layers                                                                      |
| Shield3:                     | Copper braid tinned; coverage approx. 85%                                               |
| Outer sheath:                | PVC                                                                                     |
| Sheath colour:               | Grey or black                                                                           |
| Rated voltage:               | 300 V                                                                                   |
| Testing voltage:             | Core/core: 2.0 kV; core/shield: 1.5 kV                                                  |
| Conductor resistance:        | Acc. to IEC 60228 cl. 2                                                                 |
| Insulation resistance:       | Min. 20 MΩ x km bei 20 °C                                                               |
| Current-carrying-capacity:   | Acc. to DIN VDE, s. Techn. Guidelines                                                   |
| Capacity:                    | Core/core ca. 120 nF/Km; core/shield ca. 160 nF/km                                      |
| Min. bending radius fixed:   | 7,5 x d                                                                                 |
| Min. bending radius moved:   | 15 x d                                                                                  |
| Operat. temp. fixed min/max: | -30 °C / +80 °C                                                                         |
| Operat. temp. moved min/max: | -5 °C / +80 °C                                                                          |
| Burning behavior:            | Self-extinguishing & flame-retardant acc.to IEC 60332-1                                 |
| Standard:                    | UL style 1061, UL style 2464 and CSA AWM I/II A                                         |
| Approvals:                   | UL/CSA: 80 °C - 300 V                                                                   |

## ITEM OVERVIEW

| Product No. | Dimension [n x mm²]      | Outer-Ø [mm] | Cu-Index [kg/km] | Weight [kg/1.000] | sheath colour | Variant                                               |
|-------------|--------------------------|--------------|------------------|-------------------|---------------|-------------------------------------------------------|
| 0503757     | 2 X AWG 26/7 (0,14 mm²)  | 4,2          | 14,50            | 20,00             | grey          | V1: ELITRONIC-CY LIYCY UL/CSA - DIN47100, grau / grey |
| 0503758     | 3 X AWG 26/7 (0,14 mm²)  | 4,3          | 15,50            | 28,00             | grey          | V1: ELITRONIC-CY LIYCY UL/CSA - DIN47100, grau / grey |
| 0503759     | 4 X AWG 26/7 (0,14 mm²)  | 4,6          | 16,80            | 33,00             | grey          | V1: ELITRONIC-CY LIYCY UL/CSA - DIN47100, grau / grey |
| 0503760     | 5 X AWG 26/7 (0,14 mm²)  | 4,9          | 18,00            | 38,00             | grey          | V1: ELITRONIC-CY LIYCY UL/CSA - DIN47100, grau / grey |
| 0503761     | 6 X AWG 26/7 (0,14 mm²)  | 5,2          | 24,50            | 44,00             | grey          | V1: ELITRONIC-CY LIYCY UL/CSA - DIN47100, grau / grey |
| 0503762     | 8 X AWG 26/7 (0,14 mm²)  | 5,6          | 23,70            | 56,00             | grey          | V1: ELITRONIC-CY LIYCY UL/CSA - DIN47100, grau / grey |
| 0503763     | 10 X AWG 26/7 (0,14 mm²) | 6,2          | 31,00            | 66,00             | grey          | V1: ELITRONIC-CY LIYCY UL/CSA - DIN47100, grau / grey |
| 0503765     | 12 X AWG 26/7 (0,14 mm²) | 6,4          | 32,90            | 78,00             | grey          | V1: ELITRONIC-CY LIYCY UL/CSA - DIN47100, grau / grey |
| 0503766     | 16 X AWG 26/7 (0,14 mm²) | 7,0          | 45,50            | 90,00             | grey          | V1: ELITRONIC-CY LIYCY UL/CSA - DIN47100, grau / grey |
| 0503767     | 18 X AWG 26/7 (0,14 mm²) | 7,3          | 51,30            | 104,00            | grey          | V1: ELITRONIC-CY LIYCY UL/CSA - DIN47100, grau / grey |
| 0503768     | 24 X AWG 26/7 (0,14 mm²) | 8,4          | 65,50            | 149,00            | grey          | V1: ELITRONIC-CY LIYCY UL/CSA - DIN47100, grau / grey |
| 0501969     | 25 X AWG 26/7 (0,14 mm²) | 8,4          | 67,50            | 131,00            | grey          | V1: ELITRONIC-CY LIYCY UL/CSA - DIN47100, grau / grey |
| 0506374     | 37 X AWG 26/7 (0,14 mm²) | 9,6          | 79,00            | 230,00            | grey          | V1: ELITRONIC-CY LIYCY UL/CSA - DIN47100, grau / grey |

| Product No. | Dimension [n x mm²]      | Outer-Ø [mm] | Cu-Index [kg/km] | Weight [kg/1.000] | sheath colour | Variant                                               |
|-------------|--------------------------|--------------|------------------|-------------------|---------------|-------------------------------------------------------|
| 0502366     | 2 X AWG 24/7 (0,23 mm²)  | 4,6          | 16,00            | 32,00             | grey          | V1: ELITRONIC-CY LIYCY UL/CSA - DIN47100, grau / grey |
| 0506667     | 3 X AWG 24/7 (0,23 mm²)  | 4,7          | 21,00            | 37,00             | grey          | V1: ELITRONIC-CY LIYCY UL/CSA - DIN47100, grau / grey |
| 0506606     | 4 X AWG 24/7 (0,23 mm²)  | 5,0          | 24,00            | 41,30             | grey          | V1: ELITRONIC-CY LIYCY UL/CSA - DIN47100, grau / grey |
| 0503217     | 5 X AWG 24/7 (0,23 mm²)  | 5,4          | 29,00            | 51,20             | grey          | V1: ELITRONIC-CY LIYCY UL/CSA - DIN47100, grau / grey |
| 0503773     | 6 X AWG 24/7 (0,23 mm²)  | 5,9          | 30,00            | 58,00             | grey          | V1: ELITRONIC-CY LIYCY UL/CSA - DIN47100, grau / grey |
| 0506387     | 8 X AWG 24/7 (0,23 mm²)  | 6,2          | 42,00            | 73,00             | grey          | V1: ELITRONIC-CY LIYCY UL/CSA - DIN47100, grau / grey |
| 0503775     | 10 X AWG 24/7 (0,23 mm²) | 7,0          | 46,00            | 82,00             | grey          | V1: ELITRONIC-CY LIYCY UL/CSA - DIN47100, grau / grey |
| 0506388     | 12 X AWG 24/7 (0,23 mm²) | 7,4          | 59,00            | 145,00            | grey          | V1: ELITRONIC-CY LIYCY UL/CSA - DIN47100, grau / grey |
| 0503777     | 16 X AWG 24/7 (0,23 mm²) | 8,1          | 64,00            | 124,00            | grey          | V1: ELITRONIC-CY LIYCY UL/CSA - DIN47100, grau / grey |
| 0503654     | 18 X AWG 24/7 (0,23 mm²) | 8,5          | 83,00            | 143,00            | grey          | V1: ELITRONIC-CY LIYCY UL/CSA - DIN47100, grau / grey |
| 0503779     | 24 X AWG 24/7 (0,23 mm²) | 9,8          | 114,00           | 172,00            | grey          | V1: ELITRONIC-CY LIYCY UL/CSA - DIN47100, grau / grey |
| 0503780     | 2 X AWG 22/7 (0,34 mm²)  | 4,8          | 14,90            | 32,00             | grey          | V1: ELITRONIC-CY LIYCY UL/CSA - DIN47100, grau / grey |
| 0506981     | 3 X AWG 22/7 (0,34 mm²)  | 4,9          | 18,50            | 38,00             | grey          | V1: ELITRONIC-CY LIYCY UL/CSA - DIN47100, grau / grey |
| 0502484     | 4 X AWG 22/7 (0,34 mm²)  | 5,3          | 24,80            | 44,00             | grey          | V1: ELITRONIC-CY LIYCY UL/CSA - DIN47100, grau / grey |
| 0506733     | 5 X AWG 22/7 (0,34 mm²)  | 5,8          | 28,30            | 53,00             | grey          | V1: ELITRONIC-CY LIYCY UL/CSA - DIN47100, grau / grey |
| 0506734     | 7 X AWG 22/7 (0,34 mm²)  | 6,2          | 40,20            | 71,00             | grey          | V1: ELITRONIC-CY LIYCY UL/CSA - DIN47100, grau / grey |
| 0503784     | 8 X AWG 22/7 (0,34 mm²)  | 6,7          | 52,00            | 94,00             | grey          | V1: ELITRONIC-CY LIYCY UL/CSA - DIN47100, grau / grey |
| 0507502     | 10 X AWG 22/7 (0,34 mm²) | 7,4          | 66,10            | 130,00            | grey          | V1: ELITRONIC-CY LIYCY UL/CSA - DIN47100, grau / grey |
| 0506601     | 12 X AWG 22/7 (0,34 mm²) | 7,8          | 66,50            | 120,00            | grey          | V1: ELITRONIC-CY LIYCY UL/CSA - DIN47100, grau / grey |
| 0506782     | 16 X AWG 22/7 (0,34 mm²) | 8,6          | 82,70            | 145,00            | grey          | V1: ELITRONIC-CY LIYCY UL/CSA - DIN47100, grau / grey |
| 0503787     | 21 X AWG 22/7 (0,34 mm²) | 9,4          | 102,20           | 170,00            | grey          | V1: ELITRONIC-CY LIYCY UL/CSA - DIN47100, grau / grey |
| 0503788     | 24 X AWG 22/7 (0,34 mm²) | 10,5         | 135,00           | 259,00            | grey          | V1: ELITRONIC-CY LIYCY UL/CSA - DIN47100, grau / grey |
| 0500590     | 2 X AWG 20/7 (0,56 mm²)  | 5,2          | 29,00            | 54,00             | grey          | V1: ELITRONIC-CY LIYCY UL/CSA - DIN47100, grau / grey |
| 0503790     | 3 X AWG 20/7 (0,56 mm²)  | 5,4          | 38,00            | 67,00             | grey          | V1: ELITRONIC-CY LIYCY UL/CSA - DIN47100, grau / grey |
| 0503791     | 4 X AWG 20/7 (0,56 mm²)  | 5,9          | 43,00            | 77,00             | grey          | V1: ELITRONIC-CY LIYCY UL/CSA - DIN47100, grau / grey |
| 0503792     | 5 X AWG 20/7 (0,56 mm²)  | 6,3          | 51,00            | 90,00             | grey          | V1: ELITRONIC-CY LIYCY UL/CSA - DIN47100, grau / grey |
| 0503793     | 6 X AWG 20/7 (0,56 mm²)  | 6,8          | 59,00            | 104,00            | grey          | V1: ELITRONIC-CY LIYCY UL/CSA - DIN47100, grau / grey |
| 0506315     | 8 X AWG 20/7 (0,56 mm²)  | 7,4          | 70,00            | 135,00            | grey          | V1: ELITRONIC-CY LIYCY UL/CSA - DIN47100, grau / grey |
| 0503795     | 10 X AWG 20/7 (0,56 mm²) | 8,3          | 88,00            | 160,00            | grey          | V1: ELITRONIC-CY LIYCY UL/CSA - DIN47100, grau / grey |
| 0503796     | 12 X AWG 20/7 (0,56 mm²) | 8,7          | 99,00            | 177,00            | grey          | V1: ELITRONIC-CY LIYCY UL/CSA - DIN47100, grau / grey |
| 0503797     | 16 X AWG 20/7 (0,56 mm²) | 9,5          | 129,00           | 205,00            | grey          | V1: ELITRONIC-CY LIYCY UL/CSA - DIN47100, grau / grey |
| 0503798     | 18 X AWG 20/7 (0,56 mm²) | 10,0         | 134,00           | 239,00            | grey          | V1: ELITRONIC-CY LIYCY UL/CSA - DIN47100, grau / grey |
| 0506693     | 24 X AWG 20/7 (0,56 mm²) | 11,6         | 211,00           | 352,00            | grey          | V1: ELITRONIC-CY LIYCY UL/CSA - DIN47100, grau / grey |
| 0500846     | 2 X AWG 18/19 (1,0 mm²)  | 5,9          | 43,00            | 72,00             | grey          | V1: ELITRONIC-CY LIYCY UL/CSA - DIN47100, grau / grey |
| 0503801     | 3 X AWG 18/19 (1,0 mm²)  | 6,1          | 56,00            | 90,00             | grey          | V1: ELITRONIC-CY LIYCY UL/CSA - DIN47100, grau / grey |
| 0503802     | 4 X AWG 18/19 (1,0 mm²)  | 6,6          | 68,00            | 109,00            | grey          | V1: ELITRONIC-CY LIYCY UL/CSA - DIN47100, grau / grey |
| 0503803     | 6 X AWG 18/19 (1,0 mm²)  | 7,8          | 118,00           | 171,00            | grey          | V1: ELITRONIC-CY LIYCY UL/CSA - DIN47100, grau / grey |
| 0503804     | 8 X AWG 18/19 (1,0 mm²)  | 8,4          | 140,00           | 228,00            | grey          | V1: ELITRONIC-CY LIYCY UL/CSA - DIN47100, grau / grey |
| 0506697     | 5 X AWG 26/7 (0,14 mm²)  | 4,9          | 18,00            | 38,00             | grey          | V1: ELITRONIC-CY LIYCY UL/CSA - DIN47100, grau / grey |
| 0506696     | 16 X AWG 26/7 (0,14 mm²) | 7,0          | 45,50            | 90,00             | grey          | V1: ELITRONIC-CY LIYCY UL/CSA - DIN47100, grau / grey |
| 0503715     | 2 X AWG 26/7 (0,14 mm²)  | 4,2          | 14,50            | 20,00             | black         | V2: ELITRONIC-CY LIYCY UL/CSA - IC, schwarz / black   |
| 0501828     | 3 X AWG 26/7 (0,14 mm²)  | 4,3          | 15,50            | 28,00             | black         | V2: ELITRONIC-CY LIYCY UL/CSA - IC, schwarz / black   |
| 0503717     | 4 X AWG 26/7 (0,14 mm²)  | 4,6          | 16,80            | 33,00             | black         | V2: ELITRONIC-CY LIYCY UL/CSA - IC, schwarz / black   |

| Product No. | Dimension [n x mm²]      | Outer-Ø [mm] | Cu-Index [kg/km] | Weight [kg/1.000] | sheath colour | Variant                                             |
|-------------|--------------------------|--------------|------------------|-------------------|---------------|-----------------------------------------------------|
| 0503718     | 5 X AWG 26/7 (0,14 mm²)  | 4,9          | 18,00            | 38,00             | black         | V2: ELITRONIC-CY LIYCY UL/CSA - IC, schwarz / black |
| 0503719     | 6 X AWG 26/7 (0,14 mm²)  | 5,2          | 24,50            | 44,00             | black         | V2: ELITRONIC-CY LIYCY UL/CSA - IC, schwarz / black |
| 0503720     | 8 X AWG 26/7 (0,14 mm²)  | 5,6          | 23,70            | 56,00             | black         | V2: ELITRONIC-CY LIYCY UL/CSA - IC, schwarz / black |
| 0503721     | 10 X AWG 26/7 (0,14 mm²) | 6,2          | 31,00            | 66,00             | black         | V2: ELITRONIC-CY LIYCY UL/CSA - IC, schwarz / black |
| 0503722     | 12 X AWG 26/7 (0,14 mm²) | 6,4          | 32,90            | 78,00             | black         | V2: ELITRONIC-CY LIYCY UL/CSA - IC, schwarz / black |
| 0502418     | 16 X AWG 26/7 (0,14 mm²) | 7,0          | 45,50            | 90,00             | black         | V2: ELITRONIC-CY LIYCY UL/CSA - IC, schwarz / black |
| 0503723     | 18 X AWG 26/7 (0,14 mm²) | 7,3          | 51,30            | 104,00            | black         | V2: ELITRONIC-CY LIYCY UL/CSA - IC, schwarz / black |
| 0503724     | 24 X AWG 26/7 (0,14 mm²) | 8,4          | 65,50            | 149,00            | black         | V2: ELITRONIC-CY LIYCY UL/CSA - IC, schwarz / black |
| 0503249     | 2 X AWG 24/7 (0,23 mm²)  | 4,6          | 16,00            | 32,00             | black         | V2: ELITRONIC-CY LIYCY UL/CSA - IC, schwarz / black |
| 0506662     | 3 X AWG 24/7 (0,23 mm²)  | 4,7          | 21,00            | 37,00             | black         | V2: ELITRONIC-CY LIYCY UL/CSA - IC, schwarz / black |
| 0506575     | 4 X AWG 24/7 (0,23 mm²)  | 5,0          | 24,00            | 41,30             | black         | V2: ELITRONIC-CY LIYCY UL/CSA - IC, schwarz / black |
| 0503726     | 5 X AWG 24/7 (0,23 mm²)  | 5,4          | 29,00            | 51,20             | black         | V2: ELITRONIC-CY LIYCY UL/CSA - IC, schwarz / black |
| 0501917     | 6 X AWG 24/7 (0,23 mm²)  | 5,9          | 30,00            | 58,00             | black         | V2: ELITRONIC-CY LIYCY UL/CSA - IC, schwarz / black |
| 0503727     | 8 X AWG 24/7 (0,23 mm²)  | 6,2          | 42,00            | 73,00             | black         | V2: ELITRONIC-CY LIYCY UL/CSA - IC, schwarz / black |
| 0503728     | 10 X AWG 24/7 (0,23 mm²) | 7,0          | 46,00            | 82,00             | black         | V2: ELITRONIC-CY LIYCY UL/CSA - IC, schwarz / black |
| 0503729     | 12 X AWG 24/7 (0,23 mm²) | 7,4          | 59,00            | 145,00            | black         | V2: ELITRONIC-CY LIYCY UL/CSA - IC, schwarz / black |
| 0503730     | 16 X AWG 24/7 (0,23 mm²) | 8,1          | 64,00            | 124,00            | black         | V2: ELITRONIC-CY LIYCY UL/CSA - IC, schwarz / black |
| 0503731     | 18 X AWG 24/7 (0,23 mm²) | 8,5          | 83,00            | 143,00            | black         | V2: ELITRONIC-CY LIYCY UL/CSA - IC, schwarz / black |
| 0503732     | 24 X AWG 24/7 (0,23 mm²) | 9,8          | 114,00           | 172,00            | black         | V2: ELITRONIC-CY LIYCY UL/CSA - IC, schwarz / black |
| 0503733     | 2 X AWG 22/7 (0,34 mm²)  | 4,8          | 14,90            | 32,00             | black         | V2: ELITRONIC-CY LIYCY UL/CSA - IC, schwarz / black |
| 0503734     | 3 X AWG 22/7 (0,34 mm²)  | 4,9          | 18,50            | 38,00             | black         | V2: ELITRONIC-CY LIYCY UL/CSA - IC, schwarz / black |
| 0503735     | 4 X AWG 22/7 (0,34 mm²)  | 5,3          | 24,80            | 44,00             | black         | V2: ELITRONIC-CY LIYCY UL/CSA - IC, schwarz / black |
| 0503655     | 5 X AWG 22/7 (0,34 mm²)  | 5,8          | 28,30            | 53,00             | black         | V2: ELITRONIC-CY LIYCY UL/CSA - IC, schwarz / black |
| 0503737     | 7 X AWG 22/7 (0,34 mm²)  | 6,2          | 40,20            | 71,00             | black         | V2: ELITRONIC-CY LIYCY UL/CSA - IC, schwarz / black |
| 0503738     | 8 X AWG 22/7 (0,34 mm²)  | 6,7          | 52,00            | 94,00             | black         | V2: ELITRONIC-CY LIYCY UL/CSA - IC, schwarz / black |
| 0503739     | 12 X AWG 22/7 (0,34 mm²) | 7,8          | 66,50            | 120,00            | black         | V2: ELITRONIC-CY LIYCY UL/CSA - IC, schwarz / black |
| 0503740     | 16 X AWG 22/7 (0,34 mm²) | 8,6          | 82,70            | 145,00            | black         | V2: ELITRONIC-CY LIYCY UL/CSA - IC, schwarz / black |
| 0503741     | 21 X AWG 22/7 (0,34 mm²) | 9,4          | 102,20           | 170,00            | black         | V2: ELITRONIC-CY LIYCY UL/CSA - IC, schwarz / black |
| 0503742     | 24 X AWG 22/7 (0,34 mm²) | 10,5         | 135,00           | 259,00            | black         | V2: ELITRONIC-CY LIYCY UL/CSA - IC, schwarz / black |
| 0501572     | 2 X AWG 20/7 (0,56 mm²)  | 5,2          | 29,00            | 54,00             | black         | V2: ELITRONIC-CY LIYCY UL/CSA - IC, schwarz / black |
| 0501890     | 3 X AWG 20/7 (0,56 mm²)  | 5,4          | 38,00            | 67,00             | black         | V2: ELITRONIC-CY LIYCY UL/CSA - IC, schwarz / black |
| 0500621     | 4 X AWG 20/7 (0,56 mm²)  | 5,9          | 43,00            | 77,00             | black         | V2: ELITRONIC-CY LIYCY UL/CSA - IC, schwarz / black |
| 0503746     | 5 X AWG 20/7 (0,56 mm²)  | 6,3          | 51,00            | 90,00             | black         | V2: ELITRONIC-CY LIYCY UL/CSA - IC, schwarz / black |
| 0503747     | 6 X AWG 20/7 (0,56 mm²)  | 6,8          | 59,00            | 104,00            | black         | V2: ELITRONIC-CY LIYCY UL/CSA - IC, schwarz / black |
| 0501713     | 8 X AWG 20/7 (0,56 mm²)  | 7,4          | 70,00            | 135,00            | black         | V2: ELITRONIC-CY LIYCY UL/CSA - IC, schwarz / black |
| 0503748     | 10 X AWG 20/7 (0,56 mm²) | 8,3          | 88,00            | 160,00            | black         | V2: ELITRONIC-CY LIYCY UL/CSA - IC, schwarz / black |
| 0503749     | 12 X AWG 20/7 (0,56 mm²) | 8,7          | 99,00            | 177,00            | black         | V2: ELITRONIC-CY LIYCY UL/CSA - IC, schwarz / black |
| 0501840     | 16 X AWG 20/7 (0,56 mm²) | 9,5          | 129,00           | 205,00            | black         | V2: ELITRONIC-CY LIYCY UL/CSA - IC, schwarz / black |
| 0503750     | 18 X AWG 20/7 (0,56 mm²) | 10,0         | 134,00           | 239,00            | black         | V2: ELITRONIC-CY LIYCY UL/CSA - IC, schwarz / black |
| 0503751     | 24 X AWG 20/7 (0,56 mm²) | 11,6         | 211,00           | 352,00            | black         | V2: ELITRONIC-CY LIYCY UL/CSA - IC, schwarz / black |
| 0501514     | 2 X AWG 18/19 (1,0 mm²)  | 5,9          | 43,00            | 72,00             | black         | V2: ELITRONIC-CY LIYCY UL/CSA - IC, schwarz / black |
| 0503753     | 3 X AWG 18/19 (1,0 mm²)  | 6,1          | 56,00            | 90,00             | black         | V2: ELITRONIC-CY LIYCY UL/CSA - IC, schwarz / black |
| 0503754     | 4 X AWG 18/19 (1,0 mm²)  | 6,6          | 68,00            | 109,00            | black         | V2: ELITRONIC-CY LIYCY UL/CSA - IC, schwarz / black |

| Product No. | Dimension [n x mm²]      | Outer-Ø [mm] | Cu-Index [kg/km] | Weight [kg/1.000] | sheath colour | Variant                                             |
|-------------|--------------------------|--------------|------------------|-------------------|---------------|-----------------------------------------------------|
| 0503755     | 6 X AWG 18/19 (1,0 mm²)  | 7,8          | 118,00           | 171,00            | black         | V2: ELITRONIC-CY LIYCY UL/CSA - IC, schwarz / black |
| 0506819     | 8 X AWG 18/19 (1,0 mm²)  | 8,4          | 140,00           | 228,00            | black         | V2: ELITRONIC-CY LIYCY UL/CSA - IC, schwarz / black |
| 0501145     | 12 X AWG 18/19 (1,0 mm²) | 11,2         | 152,80           | 330,00            | black         | V2: ELITRONIC-CY LIYCY UL/CSA - IC, schwarz / black |