



USE OF CABLE

UL/CSA approved PVC switching cable for internal wiring of switch boards, medical devices, electronic modules and control systems and for installation in conduits and pipes in machinery and as connecting wire for transformers and motors.



SPECIAL FEATURES

- largely resistant to acids, bases and specified types of oil
- free from lacquer damaging substances and silicone (during production)
- excellent suitable for cut-and-clamp technology by 7- or 19-wire conductor
- UL/CSA approved single core
- self-extinguishing and flame-retardant
- no direct laying on pallets, in channels or trays (exceptional as potential compensation)
- all usual standard colours available

REMARKS

- conform to RoHS
- conform to 2014/35/EU-Guideline ("Low-Voltage Directive") CE
- LABS-/silicone-free (during production)
- We are pleased to produce special versions, other dimensions, core and jacket colours on request.

PRODUCT INFORMATION

Conductor material:	Copper strand tinned
Conductor class:	Acc. to AWG-No., AWG wires and stranded conductors in technical Guidelines
Core insulation:	PVC
Core identification:	Different colours
Rated voltage:	UL Style 1007/1569: 300 V; UL-Style 1015,1284: 600 V
Testing voltage:	3 kV
Conductor resistance:	Acc. to IEC 60228
Current-carrying-capacity:	Acc to. DIN VDE, see Technical Guidelines
Min. bending radius fixed:	10 x d
Min. bending radius moved:	15 x d
Operat. temp. fixed min/max:	-40 °C / +105 °C
Burning behavior:	Self-extinguishing and flame-retardant; flammability test VW-1 UL standard 83
Standard:	UL: AWM style 1007/1569/1015
Approvals:	UL/CSA: 105 °C - 300 V / 105 °C - 600 V

ITEM OVERVIEW

Product No.	Dimension [n x mm ²]	Outer-Ø [mm]	Cu-Index [kg/km]	Weight [kg/1.000]	Single core color	Variant
0501024	1 X AWG 30 (0,055 mm ²)	1,2	0,60	0,80	blue	V1: LITZE UL/CSA - UL1007/1569
0502166	1 X AWG 30 (0,055 mm ²)	1,2	0,60	0,80	brown	V1: LITZE UL/CSA - UL1007/1569
0502167	1 X AWG 30 (0,055 mm ²)	1,2	0,60	0,80	grey	V1: LITZE UL/CSA - UL1007/1569
0502168	1 X AWG 30 (0,055 mm ²)	1,2	0,60	0,80	dark blue	V1: LITZE UL/CSA - UL1007/1569
0502169	1 X AWG 30 (0,055 mm ²)	1,2	0,60	0,80	orange	V1: LITZE UL/CSA - UL1007/1569
0502170	1 X AWG 30 (0,055 mm ²)	1,2	0,60	0,80	red	V1: LITZE UL/CSA - UL1007/1569
0502171	1 X AWG 30 (0,055 mm ²)	1,2	0,60	0,80	violet	V1: LITZE UL/CSA - UL1007/1569
0502172	1 X AWG 30 (0,055 mm ²)	1,2	0,60	0,80	white	V1: LITZE UL/CSA - UL1007/1569
0504000	1 X AWG 30 (0,055 mm ²)	1,2	0,60	0,80	green-yellow	V1: LITZE UL/CSA - UL1007/1569
0503999	1 X AWG 30 (0,055 mm ²)	1,2	0,60	0,80	black	V1: LITZE UL/CSA - UL1007/1569
0503290	1 X AWG 28 (0,084 mm ²)	1,3	0,90	2,90	blue	V1: LITZE UL/CSA - UL1007/1569
0502173	1 X AWG 28 (0,084 mm ²)	1,3	0,90	2,90	brown	V1: LITZE UL/CSA - UL1007/1569
0502174	1 X AWG 28 (0,084 mm ²)	1,3	0,90	2,90	grey	V1: LITZE UL/CSA - UL1007/1569

Product No.	Dimension [n x mm ²]	Outer-Ø [mm]	Cu-Index [kg/km]	Weight [kg/1.000]	Single core color	Variant
0502175	1 X AWG 28 (0,084 mm ²)	1,3	0,90	2,90	dark blue	V1: LITZE UL/CSA - UL1007/1569
0502176	1 X AWG 28 (0,084 mm ²)	1,3	0,90	2,90	violet	V1: LITZE UL/CSA - UL1007/1569
0502177	1 X AWG 28 (0,084 mm ²)	1,3	0,90	2,90	white	V1: LITZE UL/CSA - UL1007/1569
0500960	1 X AWG 28 (0,084 mm ²)	1,3	0,90	2,90	yellow	V1: LITZE UL/CSA - UL1007/1569
0503296	1 X AWG 28 (0,084 mm ²)	1,3	0,90	2,90	green-yellow	V1: LITZE UL/CSA - UL1007/1569
0501248	1 X AWG 28 (0,084 mm ²)	1,3	0,90	2,90	orange	V1: LITZE UL/CSA - UL1007/1569
0500962	1 X AWG 28 (0,084 mm ²)	1,3	0,90	2,90	red	V1: LITZE UL/CSA - UL1007/1569
0503288	1 X AWG 28 (0,084 mm ²)	1,3	0,90	2,90	black	V1: LITZE UL/CSA - UL1007/1569
0504002	1 X AWG 28 (0,084 mm ²)	1,3	0,90	2,90	black	V1: LITZE UL/CSA - UL1007/1569
0506454	1 X AWG 26 (0,13 mm ²)	1,4	1,40	3,20	blue	V1: LITZE UL/CSA - UL1007/1569
0502178	1 X AWG 26 (0,13 mm ²)	1,4	1,40	3,20	dark blue	V1: LITZE UL/CSA - UL1007/1569
0502346	1 X AWG 26 (0,13 mm ²)	1,4	1,40	3,20	brown	V1: LITZE UL/CSA - UL1007/1569
0501966	1 X AWG 26 (0,13 mm ²)	1,4	1,40	3,20	yellow	V1: LITZE UL/CSA - UL1007/1569
0501541	1 X AWG 26 (0,13 mm ²)	1,4	1,40	3,20	grey	V1: LITZE UL/CSA - UL1007/1569
0501539	1 X AWG 26 (0,13 mm ²)	1,4	1,40	3,20	green	V1: LITZE UL/CSA - UL1007/1569
0504003	1 X AWG 26 (0,13 mm ²)	1,4	1,40	3,20	green-yellow	V1: LITZE UL/CSA - UL1007/1569
0503073	1 X AWG 26 (0,13 mm ²)	1,4	1,40	3,20	orange	V1: LITZE UL/CSA - UL1007/1569
0501538	1 X AWG 26 (0,13 mm ²)	1,4	1,40	3,20	red	V1: LITZE UL/CSA - UL1007/1569
0501537	1 X AWG 26 (0,13 mm ²)	1,4	1,40	3,20	black	V1: LITZE UL/CSA - UL1007/1569
0507468	1 X AWG 26 (0,13 mm ²)	1,4	1,40	3,20	violet	V1: LITZE UL/CSA - UL1007/1569
0506624	1 X AWG 26 (0,13 mm ²)	1,4	1,40	3,20	white	V1: LITZE UL/CSA - UL1007/1569
0501535	1 X AWG 24 (0,21 mm ²)	1,5	2,10	4,50	blue	V1: LITZE UL/CSA - UL1007/1569
0502397	1 X AWG 24 (0,21 mm ²)	1,5	2,10	4,50	brown	V1: LITZE UL/CSA - UL1007/1569
0501741	1 X AWG 24 (0,21 mm ²)	1,5	2,10	4,50	yellow	V1: LITZE UL/CSA - UL1007/1569
0500556	1 X AWG 24 (0,21 mm ²)	1,5	2,10	4,50	grey	V1: LITZE UL/CSA - UL1007/1569
0502398	1 X AWG 24 (0,21 mm ²)	1,5	2,10	4,50	green	V1: LITZE UL/CSA - UL1007/1569
0506873	1 X AWG 24 (0,21 mm ²)	1,5	2,10	4,50	green-yellow	V1: LITZE UL/CSA - UL1007/1569
0506874	1 X AWG 24 (0,21 mm ²)	1,5	2,10	4,50	orange	V1: LITZE UL/CSA - UL1007/1569
0507380	1 X AWG 24 (0,21 mm ²)	1,5	2,10	4,50	pink	V1: LITZE UL/CSA - UL1007/1569
0501540	1 X AWG 24 (0,21 mm ²)	1,5	2,10	4,50	red	V1: LITZE UL/CSA - UL1007/1569
0501534	1 X AWG 24 (0,21 mm ²)	1,5	2,10	4,50	black	V1: LITZE UL/CSA - UL1007/1569
0503276	1 X AWG 24 (0,21 mm ²)	1,5	2,10	4,50	violet	V1: LITZE UL/CSA - UL1007/1569
0501863	1 X AWG 24 (0,21 mm ²)	1,5	2,10	4,50	white	V1: LITZE UL/CSA - UL1007/1569
0501977	1 X AWG 22 (0,33 mm ²)	1,6	3,30	5,80	blue	V1: LITZE UL/CSA - UL1007/1569
0502013	1 X AWG 22 (0,33 mm ²)	1,6	3,30	5,80	dark blue	V1: LITZE UL/CSA - UL1007/1569
0502200	1 X AWG 22 (0,33 mm ²)	1,6	3,30	5,80	red-blue	V1: LITZE UL/CSA - UL1007/1569
0502201	1 X AWG 22 (0,33 mm ²)	1,6	3,30	5,80	grey-pink	V1: LITZE UL/CSA - UL1007/1569
0502314	1 X AWG 22 (0,33 mm ²)	1,6	3,30	5,80	brown	V1: LITZE UL/CSA - UL1007/1569
0502313	1 X AWG 22 (0,33 mm ²)	1,6	3,30	5,80	yellow	V1: LITZE UL/CSA - UL1007/1569
0502437	1 X AWG 22 (0,33 mm ²)	1,6	3,30	5,80	grey	V1: LITZE UL/CSA - UL1007/1569
0501976	1 X AWG 22 (0,33 mm ²)	1,6	3,30	5,80	green	V1: LITZE UL/CSA - UL1007/1569
0504005	1 X AWG 22 (0,33 mm ²)	1,6	3,30	5,80	green-yellow	V1: LITZE UL/CSA - UL1007/1569
0502458	1 X AWG 22 (0,33 mm ²)	1,6	3,30	5,80	orange	V1: LITZE UL/CSA - UL1007/1569

Product No.	Dimension [n x mm ²]	Outer-Ø [mm]	Cu-Index [kg/km]	Weight [kg/1.000]	Single core color	Variant
0506669	1 X AWG 22 (0,33 mm ²)	1,6	3,30	5,80	pink	V1: LITZE UL/CSA - UL1007/1569
0501894	1 X AWG 22 (0,33 mm ²)	1,6	3,30	5,80	red	V1: LITZE UL/CSA - UL1007/1569
0501533	1 X AWG 22 (0,33 mm ²)	1,6	3,30	5,80	black	V1: LITZE UL/CSA - UL1007/1569
0506648	1 X AWG 22 (0,33 mm ²)	1,6	3,30	5,80	violet	V1: LITZE UL/CSA - UL1007/1569
0501552	1 X AWG 22 (0,33 mm ²)	1,6	3,30	5,80	white	V1: LITZE UL/CSA - UL1007/1569
0502604	1 X AWG 22 (0,33 mm ²)	1,6	3,30	5,80	white	V1: LITZE UL/CSA - UL1007/1569
0501724	1 X AWG 20 (0,56 mm ²)	1,9	5,50	8,80	blue	V1: LITZE UL/CSA - UL1007/1569
0507469	1 X AWG 20 (0,56 mm ²)	1,9	5,50	8,80	brown	V1: LITZE UL/CSA - UL1007/1569
0501591	1 X AWG 20 (0,56 mm ²)	1,9	5,50	8,80	dark blue	V1: LITZE UL/CSA - UL1007/1569
0503242	1 X AWG 20 (0,56 mm ²)	1,9	5,50	8,80	yellow	V1: LITZE UL/CSA - UL1007/1569
0501589	1 X AWG 20 (0,56 mm ²)	1,9	5,50	8,80	grey	V1: LITZE UL/CSA - UL1007/1569
0502338	1 X AWG 20 (0,56 mm ²)	1,9	5,50	8,80	green	V1: LITZE UL/CSA - UL1007/1569
0501592	1 X AWG 20 (0,56 mm ²)	1,9	5,50	8,80	green-yellow	V1: LITZE UL/CSA - UL1007/1569
0507470	1 X AWG 20 (0,56 mm ²)	1,9	5,50	8,80	orange	V1: LITZE UL/CSA - UL1007/1569
0501245	1 X AWG 20 (0,56 mm ²)	1,9	5,50	8,80	red	V1: LITZE UL/CSA - UL1007/1569
0501244	1 X AWG 20 (0,56 mm ²)	1,9	5,50	8,80	black	V1: LITZE UL/CSA - UL1007/1569
0506719	1 X AWG 20 (0,56 mm ²)	1,9	5,50	8,80	violet	V1: LITZE UL/CSA - UL1007/1569
0501590	1 X AWG 20 (0,56 mm ²)	1,9	5,50	8,80	white	V1: LITZE UL/CSA - UL1007/1569
0501249	1 X AWG 20 (0,56 mm ²)	1,9	5,50	8,80	pink	V1: LITZE UL/CSA - UL1007/1569
0500051	1 X AWG 18 (0,82 mm ²)	2,2	8,50	12,50	blue	V1: LITZE UL/CSA - UL1007/1569
0500052	1 X AWG 18 (0,82 mm ²)	2,2	8,50	12,50	brown	V1: LITZE UL/CSA - UL1007/1569
0500053	1 X AWG 18 (0,82 mm ²)	2,2	8,50	12,50	yellow	V1: LITZE UL/CSA - UL1007/1569
0500056	1 X AWG 18 (0,82 mm ²)	2,2	8,50	12,50	grey	V1: LITZE UL/CSA - UL1007/1569
0500054	1 X AWG 18 (0,82 mm ²)	2,2	8,50	12,50	green	V1: LITZE UL/CSA - UL1007/1569
0500055	1 X AWG 18 (0,82 mm ²)	2,2	8,50	12,50	green-yellow	V1: LITZE UL/CSA - UL1007/1569
0500057	1 X AWG 18 (0,82 mm ²)	2,2	8,50	12,50	orange	V1: LITZE UL/CSA - UL1007/1569
0500058	1 X AWG 18 (0,82 mm ²)	2,2	8,50	12,50	red	V1: LITZE UL/CSA - UL1007/1569
0500059	1 X AWG 18 (0,82 mm ²)	2,2	8,50	12,50	black	V1: LITZE UL/CSA - UL1007/1569
0501373	1 X AWG 18 (0,82 mm ²)	2,2	8,50	12,50	pink	V1: LITZE UL/CSA - UL1007/1569
0507528	1 X AWG 18 (0,82 mm ²)	2,2	8,50	12,50	violet	V1: LITZE UL/CSA - UL1007/1569
0500061	1 X AWG 18 (0,82 mm ²)	2,2	8,50	12,50	white	V1: LITZE UL/CSA - UL1007/1569
0501544	1 X AWG 16 (1,31 mm ²)	2,6	13,50	18,60	blue	V1: LITZE UL/CSA - UL1007/1569
0506422	1 X AWG 16 (1,31 mm ²)	2,6	13,50	18,60	brown	V1: LITZE UL/CSA - UL1007/1569
0502179	1 X AWG 16 (1,31 mm ²)	2,6	8,50	18,60	dark blue	V1: LITZE UL/CSA - UL1007/1569
0502180	1 X AWG 16 (1,31 mm ²)	2,6	13,50	18,60	dark blue	V1: LITZE UL/CSA - UL1007/1569
0502181	1 X AWG 16 (1,31 mm ²)	2,6	13,50	18,60	green	V1: LITZE UL/CSA - UL1007/1569
0502182	1 X AWG 16 (1,31 mm ²)	2,6	13,50	18,60	orange	V1: LITZE UL/CSA - UL1007/1569
0501098	1 X AWG 16 (1,31 mm ²)	2,6	13,50	18,60	yellow	V1: LITZE UL/CSA - UL1007/1569
0501587	1 X AWG 16 (1,31 mm ²)	2,6	13,50	18,60	grey	V1: LITZE UL/CSA - UL1007/1569
0501532	1 X AWG 16 (1,31 mm ²)	2,6	13,50	18,60	green-yellow	V1: LITZE UL/CSA - UL1007/1569
0501543	1 X AWG 16 (1,31 mm ²)	2,6	13,50	18,60	red	V1: LITZE UL/CSA - UL1007/1569
0501542	1 X AWG 16 (1,31 mm ²)	2,6	13,50	18,60	black	V1: LITZE UL/CSA - UL1007/1569
0500581	1 X AWG 16 (1,31 mm ²)	2,6	13,50	18,60	violet	V1: LITZE UL/CSA - UL1007/1569

Product No.	Dimension [n x mm ²]	Outer-Ø [mm]	Cu-Index [kg/km]	Weight [kg/1.000]	Single core color	Variant
0501588	1 X AWG 16 (1,31 mm ²)	2,6	13,50	18,60	white	V1: LITZE UL/CSA - UL1007/1569
0501581	1 X AWG 24 (0,21 mm ²)	2,2	2,10	7,20	blue	V2: LITZE UL/CSA - UL1015
0501058	1 X AWG 24 (0,21 mm ²)	2,2	2,10	7,20	brown	V2: LITZE UL/CSA - UL1015
0501506	1 X AWG 24 (0,21 mm ²)	2,2	2,10	7,20	yellow	V2: LITZE UL/CSA - UL1015
0501747	1 X AWG 24 (0,21 mm ²)	2,2	2,10	7,20	green-yellow	V2: LITZE UL/CSA - UL1015
0501055	1 X AWG 24 (0,21 mm ²)	2,2	2,10	7,20	red	V2: LITZE UL/CSA - UL1015
0503239	1 X AWG 24 (0,21 mm ²)	2,2	2,10	7,20	black	V2: LITZE UL/CSA - UL1015
0501057	1 X AWG 24 (0,21 mm ²)	2,2	2,10	7,20	white	V2: LITZE UL/CSA - UL1015
0501422	1 X AWG 24 (0,21 mm ²)	2,2	2,10	7,20	green	V2: LITZE UL/CSA - UL1015
0502020	1 X AWG 24 (0,21 mm ²)	2,2	2,10	7,20	grey	V2: LITZE UL/CSA - UL1015
0502021	1 X AWG 24 (0,21 mm ²)	2,2	2,10	7,20	dark blue	V2: LITZE UL/CSA - UL1015
0502022	1 X AWG 24 (0,21 mm ²)	2,2	2,10	7,20	green	V2: LITZE UL/CSA - UL1015
0502023	1 X AWG 24 (0,21 mm ²)	2,2	2,10	7,20	orange	V2: LITZE UL/CSA - UL1015
0502029	1 X AWG 24 (0,21 mm ²)	2,2	2,10	7,20	violet	V2: LITZE UL/CSA - UL1015
0502097	1 X AWG 24 (0,21 mm ²)	2,2	2,10	7,20	pink	V2: LITZE UL/CSA - UL1015
0501887	1 X AWG 22 (0,33 mm ²)	2,4	3,30	9,00	blue	V2: LITZE UL/CSA - UL1015
0500003	1 X AWG 22 (0,33 mm ²)	2,4	3,30	9,00	yellow	V2: LITZE UL/CSA - UL1015
0502400	1 X AWG 22 (0,33 mm ²)	2,4	3,30	9,00	grey	V2: LITZE UL/CSA - UL1015
0501883	1 X AWG 22 (0,33 mm ²)	2,4	3,30	9,00	green	V2: LITZE UL/CSA - UL1015
0504010	1 X AWG 22 (0,33 mm ²)	2,4	3,30	9,00	green-yellow	V2: LITZE UL/CSA - UL1015
0501884	1 X AWG 22 (0,33 mm ²)	2,4	3,30	9,00	black	V2: LITZE UL/CSA - UL1015
0501885	1 X AWG 22 (0,33 mm ²)	2,4	3,30	9,00	violet	V2: LITZE UL/CSA - UL1015
0501908	1 X AWG 22 (0,33 mm ²)	2,4	3,30	9,00	white	V2: LITZE UL/CSA - UL1015
0502030	1 X AWG 22 (0,33 mm ²)	2,4	3,30	9,00	brown	V2: LITZE UL/CSA - UL1015
0502031	1 X AWG 22 (0,33 mm ²)	2,4	3,30	9,00	dark blue	V2: LITZE UL/CSA - UL1015
0502032	1 X AWG 22 (0,33 mm ²)	2,4	3,30	9,00	orange	V2: LITZE UL/CSA - UL1015
0502092	1 X AWG 22 (0,33 mm ²)	2,4	3,30	9,00	pink	V2: LITZE UL/CSA - UL1015
0502093	1 X AWG 22 (0,33 mm ²)	2,4	3,30	9,00	red	V2: LITZE UL/CSA - UL1015
0501798	1 X AWG 20 (0,56 mm ²)	2,7	5,50	12,80	blue	V2: LITZE UL/CSA - UL1015
0502210	1 X AWG 20 (0,56 mm ²)	2,7	7,20	12,80	blue-white	V2: LITZE UL/CSA - UL1015
0507567	1 X AWG 20 (0,56 mm ²)	2,7	5,50	12,80	brown	V2: LITZE UL/CSA - UL1015
0501748	1 X AWG 20 (0,56 mm ²)	2,7	5,50	12,80	yellow	V2: LITZE UL/CSA - UL1015
0507566	1 X AWG 20 (0,56 mm ²)	2,7	5,50	12,80	grey	V2: LITZE UL/CSA - UL1015
0501784	1 X AWG 20 (0,56 mm ²)	2,7	5,50	12,80	green	V2: LITZE UL/CSA - UL1015
0501973	1 X AWG 20 (0,56 mm ²)	2,7	5,50	12,80	green-yellow	V2: LITZE UL/CSA - UL1015
0507568	1 X AWG 20 (0,56 mm ²)	2,7	5,50	12,80	orange	V2: LITZE UL/CSA - UL1015
0501972	1 X AWG 20 (0,56 mm ²)	2,7	5,50	12,80	red	V2: LITZE UL/CSA - UL1015
0501780	1 X AWG 20 (0,56 mm ²)	2,7	5,50	12,80	black	V2: LITZE UL/CSA - UL1015
0506331	1 X AWG 20 (0,56 mm ²)	2,7	5,50	12,80	violet	V2: LITZE UL/CSA - UL1015
0503065	1 X AWG 20 (0,56 mm ²)	2,7	5,50	12,80	white	V2: LITZE UL/CSA - UL1015
0502094	1 X AWG 20 (0,56 mm ²)	2,7	5,50	12,80	dark blue	V2: LITZE UL/CSA - UL1015
0502095	1 X AWG 20 (0,56 mm ²)	2,7	5,50	12,80	pink	V2: LITZE UL/CSA - UL1015
0502096	1 X AWG 20 (0,56 mm ²)	2,7	5,50	12,80	white-blue	V2: LITZE UL/CSA - UL1015

Product No.	Dimension [n x mm ²]	Outer-Ø [mm]	Cu-Index [kg/km]	Weight [kg/1.000]	Single core color	Variant
0500555	1 X AWG 18 (0,82 mm ²)	3,0	8,50	16,50	blue	V2: LITZE UL/CSA - UL1015
0501101	1 X AWG 18 (0,82 mm ²)	3,0	8,00	16,50	blue-white	V2: LITZE UL/CSA - UL1015
0500044	1 X AWG 18 (0,82 mm ²)	3,0	8,50	16,50	brown	V2: LITZE UL/CSA - UL1015
0501847	1 X AWG 18 (0,82 mm ²)	3,0	8,50	16,50	dark blue	V2: LITZE UL/CSA - UL1015
0500585	1 X AWG 18 (0,82 mm ²)	3,0	8,50	16,50	yellow	V2: LITZE UL/CSA - UL1015
0500048	1 X AWG 18 (0,82 mm ²)	3,0	8,50	16,50	grey	V2: LITZE UL/CSA - UL1015
0500046	1 X AWG 18 (0,82 mm ²)	3,0	8,50	16,50	green	V2: LITZE UL/CSA - UL1015
0500047	1 X AWG 18 (0,82 mm ²)	3,0	8,50	16,50	green-yellow	V2: LITZE UL/CSA - UL1015
0501698	1 X AWG 18 (0,82 mm ²)	3,0	8,50	16,50	orange	V2: LITZE UL/CSA - UL1015
0507569	1 X AWG 18 (0,82 mm ²)	3,0	8,50	16,50	pink	V2: LITZE UL/CSA - UL1015
0500049	1 X AWG 18 (0,82 mm ²)	3,0	8,50	16,50	red	V2: LITZE UL/CSA - UL1015
0500050	1 X AWG 18 (0,82 mm ²)	3,0	8,50	16,50	black	V2: LITZE UL/CSA - UL1015
0501785	1 X AWG 18 (0,82 mm ²)	3,0	8,50	16,50	violet	V2: LITZE UL/CSA - UL1015
0500063	1 X AWG 18 (0,82 mm ²)	3,0	8,50	16,50	white	V2: LITZE UL/CSA - UL1015
0502098	1 X AWG 18 (0,82 mm ²)	3,0	8,50	16,50	white-blue	V2: LITZE UL/CSA - UL1015
0500039	1 X AWG 16 (1,31 mm ²)	3,3	13,50	24,10	blue	V2: LITZE UL/CSA - UL1015
0501508	1 X AWG 16 (1,31 mm ²)	3,3	13,50	24,10	brown	V2: LITZE UL/CSA - UL1015
0501068	1 X AWG 16 (1,31 mm ²)	3,3	13,50	24,10	dark blue-white	V2: LITZE UL/CSA - UL1015
0500040	1 X AWG 16 (1,31 mm ²)	3,3	13,50	24,10	grey	V2: LITZE UL/CSA - UL1015
0501494	1 X AWG 16 (1,31 mm ²)	3,3	13,50	24,10	green	V2: LITZE UL/CSA - UL1015
0501509	1 X AWG 16 (1,31 mm ²)	3,3	13,50	24,10	green-yellow	V2: LITZE UL/CSA - UL1015
0501510	1 X AWG 16 (1,31 mm ²)	3,3	13,50	24,10	red	V2: LITZE UL/CSA - UL1015
0501067	1 X AWG 16 (1,31 mm ²)	3,3	13,50	24,10	red-white	V2: LITZE UL/CSA - UL1015
0501507	1 X AWG 16 (1,31 mm ²)	3,3	13,50	24,10	black	V2: LITZE UL/CSA - UL1015
0501891	1 X AWG 16 (1,31 mm ²)	3,3	13,50	24,10	black	V2: LITZE UL/CSA - UL1015
0500041	1 X AWG 16 (1,31 mm ²)	3,3	13,50	24,10	violet	V2: LITZE UL/CSA - UL1015
0500042	1 X AWG 16 (1,31 mm ²)	3,3	13,50	24,10	white	V2: LITZE UL/CSA - UL1015
0502099	1 X AWG 16 (1,31 mm ²)	3,3	13,50	24,10	dark blue	V2: LITZE UL/CSA - UL1015
0502100	1 X AWG 16 (1,31 mm ²)	3,3	13,50	24,10	yellow	V2: LITZE UL/CSA - UL1015
0502101	1 X AWG 16 (1,31 mm ²)	3,3	13,50	24,10	orange	V2: LITZE UL/CSA - UL1015
0502102	1 X AWG 16 (1,31 mm ²)	3,3	13,50	24,10	pink	V2: LITZE UL/CSA - UL1015
0502103	1 X AWG 16 (1,31 mm ²)	3,3	13,50	24,10	white-blue	V2: LITZE UL/CSA - UL1015
0500022	1 X AWG 14 (2,15 mm ²)	3,4	20,00	30,40	blue	V2: LITZE UL/CSA - UL1015
0500032	1 X AWG 14 (2,15 mm ²)	3,4	20,00	30,40	brown	V2: LITZE UL/CSA - UL1015
0501073	1 X AWG 14 (2,15 mm ²)	3,4	20,00	30,40	dark blue-white	V2: LITZE UL/CSA - UL1015
0500033	1 X AWG 14 (2,15 mm ²)	3,4	20,00	30,40	yellow	V2: LITZE UL/CSA - UL1015
0501905	1 X AWG 14 (2,15 mm ²)	3,4	20,00	30,40	grey	V2: LITZE UL/CSA - UL1015
0500024	1 X AWG 14 (2,15 mm ²)	3,4	20,00	30,40	green	V2: LITZE UL/CSA - UL1015
0500028	1 X AWG 14 (2,15 mm ²)	3,4	20,00	30,40	green-yellow	V2: LITZE UL/CSA - UL1015
0500023	1 X AWG 14 (2,15 mm ²)	3,4	20,00	30,40	green-yellow	V2: LITZE UL/CSA - UL1015
0500025	1 X AWG 14 (2,15 mm ²)	3,4	20,00	30,40	red	V2: LITZE UL/CSA - UL1015
0500026	1 X AWG 14 (2,15 mm ²)	3,4	20,00	30,40	black	V2: LITZE UL/CSA - UL1015
0500038	1 X AWG 14 (2,15 mm ²)	3,4	20,00	30,40	white	V2: LITZE UL/CSA - UL1015

Product No.	Dimension [n x mm ²]	Outer-Ø [mm]	Cu-Index [kg/km]	Weight [kg/1.000]	Single core color	Variant
0502104	1 X AWG 14 (2,15 mm ²)	3,4	20,00	30,40	dark blue	V2: LITZE UL/CSA - UL1015
0502105	1 X AWG 14 (2,15 mm ²)	3,4	20,00	30,40	orange	V2: LITZE UL/CSA - UL1015
0502106	1 X AWG 14 (2,15 mm ²)	3,4	20,00	30,40	pink	V2: LITZE UL/CSA - UL1015
0502107	1 X AWG 14 (2,15 mm ²)	3,4	20,00	30,40	violet	V2: LITZE UL/CSA - UL1015
0502108	1 X AWG 14 (2,15 mm ²)	3,4	20,00	30,40	white-blue	V2: LITZE UL/CSA - UL1015
0503050	1 X AWG 12 (3,44 mm ²)	4,2	32,00	42,20	blue	V2: LITZE UL/CSA - UL1015
0503058	1 X AWG 12 (3,44 mm ²)	4,2	32,00	42,20	yellow	V2: LITZE UL/CSA - UL1015
0501622	1 X AWG 12 (3,44 mm ²)	4,2	32,00	42,20	grey	V2: LITZE UL/CSA - UL1015
0501740	1 X AWG 12 (3,44 mm ²)	4,2	32,00	42,20	green-yellow	V2: LITZE UL/CSA - UL1015
0506633	1 X AWG 12 (3,44 mm ²)	4,2	32,00	42,20	red	V2: LITZE UL/CSA - UL1015
0501074	1 X AWG 12 (3,44 mm ²)	4,2	32,00	42,20	red-white	V2: LITZE UL/CSA - UL1015
0500020	1 X AWG 12 (3,44 mm ²)	4,2	32,00	42,20	black	V2: LITZE UL/CSA - UL1015
0501459	1 X AWG 12 (3,44 mm ²)	4,2	32,00	42,20	white	V2: LITZE UL/CSA - UL1015
0502109	1 X AWG 12 (3,44 mm ²)	4,2	32,00	42,20	brown	V2: LITZE UL/CSA - UL1015
0502111	1 X AWG 12 (3,44 mm ²)	4,2	32,00	42,20	dark blue	V2: LITZE UL/CSA - UL1015
0502112	1 X AWG 12 (3,44 mm ²)	4,2	32,00	42,20	green	V2: LITZE UL/CSA - UL1015
0502113	1 X AWG 12 (3,44 mm ²)	4,2	32,00	42,20	orange	V2: LITZE UL/CSA - UL1015
0502114	1 X AWG 12 (3,44 mm ²)	4,2	32,00	42,20	pink	V2: LITZE UL/CSA - UL1015
0502115	1 X AWG 12 (3,44 mm ²)	4,2	32,00	42,20	violet	V2: LITZE UL/CSA - UL1015
0502117	1 X AWG 12 (3,44 mm ²)	4,2	32,00	42,20	white-blue	V2: LITZE UL/CSA - UL1015
0501814	1 X AWG 10 (5,37 mm ²)	5,1	52,00	65,00	blue	V2: LITZE UL/CSA - UL1015
0501873	1 X AWG 10 (5,37 mm ²)	5,1	52,00	65,00	brown	V2: LITZE UL/CSA - UL1015
0507199	1 X AWG 10 (5,37 mm ²)	5,1	52,00	65,00	grey	V2: LITZE UL/CSA - UL1015
0500916	1 X AWG 10 (5,37 mm ²)	5,1	52,00	65,00	green	V2: LITZE UL/CSA - UL1015
0500018	1 X AWG 10 (5,37 mm ²)	5,1	52,00	65,00	green-yellow	V2: LITZE UL/CSA - UL1015
0501846	1 X AWG 10 (5,37 mm ²)	5,1	52,00	65,00	orange	V2: LITZE UL/CSA - UL1015
0503603	1 X AWG 10 (5,37 mm ²)	5,1	52,00	65,00	red	V2: LITZE UL/CSA - UL1015
0500019	1 X AWG 10 (5,37 mm ²)	5,1	52,00	65,00	black	V2: LITZE UL/CSA - UL1015
0501954	1 X AWG 10 (5,37 mm ²)	5,1	52,00	65,00	white	V2: LITZE UL/CSA - UL1015
0502120	1 X AWG 10 (5,37 mm ²)	5,1	52,00	65,00	dark blue	V2: LITZE UL/CSA - UL1015
0502121	1 X AWG 10 (5,37 mm ²)	5,1	52,00	65,00	yellow	V2: LITZE UL/CSA - UL1015
0502122	1 X AWG 10 (5,37 mm ²)	5,1	52,00	65,00	pink	V2: LITZE UL/CSA - UL1015
0502123	1 X AWG 10 (5,37 mm ²)	5,1	52,00	65,00	violet	V2: LITZE UL/CSA - UL1015
0507412	1 X AWG 8 (8,39 mm ²)	6,6	84,00	110,00	blue	V2: LITZE UL/CSA - UL1015
0507201	1 X AWG 8 (8,39 mm ²)	6,6	84,00	110,00	brown	V2: LITZE UL/CSA - UL1015
0502428	1 X AWG 8 (8,39 mm ²)	6,6	84,00	110,00	green-yellow	V2: LITZE UL/CSA - UL1015
0501146	1 X AWG 8 (8,39 mm ²)	6,6	84,00	110,00	red	V2: LITZE UL/CSA - UL1015
0501958	1 X AWG 8 (8,39 mm ²)	6,6	84,00	110,00	black	V2: LITZE UL/CSA - UL1015
0502124	1 X AWG 8 (8,39 mm ²)	6,6	84,00	110,00	grey	V2: LITZE UL/CSA - UL1015
0502125	1 X AWG 8 (8,39 mm ²)	6,6	84,00	110,00	dark blue	V2: LITZE UL/CSA - UL1015
0502126	1 X AWG 8 (8,39 mm ²)	6,6	84,00	110,00	yellow	V2: LITZE UL/CSA - UL1015
0502128	1 X AWG 8 (8,39 mm ²)	6,6	84,00	110,00	orange	V2: LITZE UL/CSA - UL1015
0502127	1 X AWG 8 (8,39 mm ²)	6,6	84,00	110,00	green	V2: LITZE UL/CSA - UL1015

Product No.	Dimension [n x mm ²]	Outer-Ø [mm]	Cu-Index [kg/km]	Weight [kg/1.000]	Single core color	Variant
0502130	1 X AWG 8 (8,39 mm ²)	6,6	84,00	110,00	pink	V2: LITZE UL/CSA - UL1015
0502131	1 X AWG 8 (8,39 mm ²)	6,6	84,00	110,00	violet	V2: LITZE UL/CSA - UL1015
0502132	1 X AWG 8 (8,39 mm ²)	6,6	84,00	110,00	white	V2: LITZE UL/CSA - UL1015
0502133	1 X AWG 6 (13,47 mm ²)	8,7	137,00	180,00	green-yellow	V2: LITZE UL/CSA - UL1015
0503088	1 X AWG 6 (13,47 mm ²)	8,7	137,00	180,00	black	V2: LITZE UL/CSA - UL1015
0502134	1 X AWG 6 (13,47 mm ²)	8,7	137,00	180,00	black	V2: LITZE UL/CSA - UL1015
0503089	1 X AWG 6 (13,47 mm ²)	8,7	137,00	180,00	yellow	V2: LITZE UL/CSA - UL1015
0501957	1 X AWG 4 (21,13 mm ²)	9,9	212,00	287,00	black	V2: LITZE UL/CSA - UL1015
0502135	1 X AWG 4 (21,13 mm ²)	9,9	212,00	287,00	green-yellow	V2: LITZE UL/CSA - UL1015
0502138	1 X AWG 2 (33,57 mm ²)	11,0	324,00	384,00	green-yellow	V2: LITZE UL/CSA - UL1015
0506564	1 X AWG 2 (33,57 mm ²)	11,0	324,00	384,00	black	V2: LITZE UL/CSA - UL1015
0502139	1 X AWG 1 (42,62 mm ²)	12,8	410,00	410,00	green-yellow	V2: LITZE UL/CSA - UL1015
0502140	1 X AWG 1 (42,62 mm ²)	12,8	410,00	410,00	black	V2: LITZE UL/CSA - UL1015
0502141	1 X AWG 2/0 (64,06 mm ²)	15,5	616,00	670,00	green-yellow	V2: LITZE UL/CSA - UL1015
0502142	1 X AWG 2/0 (64,06 mm ²)	15,5	616,00	670,00	black	V2: LITZE UL/CSA - UL1015
0501046	1 X AWG 1 (42,62 mm ²)	12,8	410,00	496,00	blue	V3: LITZE UL/CSA - UL1284
0504012	1 X AWG 1 (42,62 mm ²)	12,8	410,00	496,00	green-yellow	V3: LITZE UL/CSA - UL1284
0504013	1 X AWG 1 (42,62 mm ²)	12,8	410,00	496,00	black	V3: LITZE UL/CSA - UL1284